

XI'AN FUNCTION MATERIAL GROUP CO., LTD

Safety Data Sheet Aluminum Cobalt Alloy

1. Product and Company Identification		
Trade Name:	Aluminum cob	alt alloy
Chemical Formula:	Al/Co	•
Recommended Use:	Scientific resea	rch and development
Manufacturer/Supplier:	XI'AN FUNCT	FION MATERIAL GROUP CO., LTD
Street:		e Valley, High-Tech Zone
City:	XI'AN	
State:	Shannxi	
Zip Code:	710077	
Country:	China	
Tel #:	+86-29-889938	370/+86-13519132051
	2. Hazards Ide	entification
Signal Word:	Danger	
Hazard Statements:	H261 In contac H334 May caus if inhaled.	fire spontaneously if exposed to air. et with water releases flammable gas. se allergy or asthma symptoms or breathing difficultie
	H250 Catches H261 In contac H334 May caus if inhaled. H317 May caus	fire spontaneously if exposed to air. et with water releases flammable gas. se allergy or asthma symptoms or breathing difficultie se an allergic skin reaction.
Hazard Statements: Precautionary Statements:	H250 Catches t H261 In contac H334 May caus if inhaled. H317 May caus P210 Keep awa	fire spontaneously if exposed to air. et with water releases flammable gas. se allergy or asthma symptoms or breathing difficultie
	H250 Catches t H261 In contac H334 May caus if inhaled. H317 May caus P210 Keep awa smoking.	fire spontaneously if exposed to air. et with water releases flammable gas. se allergy or asthma symptoms or breathing difficultie se an allergic skin reaction. ay from heat/sparks/open flames/hot surfaces – No
	H250 Catches H H261 In contac H334 May caus if inhaled. H317 May caus P210 Keep awa smoking. P222 Do not al	fire spontaneously if exposed to air. et with water releases flammable gas. se allergy or asthma symptoms or breathing difficultie se an allergic skin reaction. ay from heat/sparks/open flames/hot surfaces – No low contact with air.
	H250 Catches H H261 In contac H334 May caus if inhaled. H317 May caus P210 Keep awa smoking. P222 Do not al P231+P232: Ha	fire spontaneously if exposed to air. et with water releases flammable gas. se allergy or asthma symptoms or breathing difficultie se an allergic skin reaction. ay from heat/sparks/open flames/hot surfaces – No low contact with air. andle under inert gas. Protect from moisture
	H250 Catches t H261 In contac H334 May caus if inhaled. H317 May caus P210 Keep awa smoking. P222 Do not al P231+P232: Ha P363 Wash cor	fire spontaneously if exposed to air. et with water releases flammable gas. se allergy or asthma symptoms or breathing difficultie se an allergic skin reaction. ay from heat/sparks/open flames/hot surfaces – No low contact with air. andle under inert gas. Protect from moisture ntaminated clothing before reuse.
	H250 Catches H H261 In contac H334 May caus if inhaled. H317 May caus P210 Keep awa smoking. P222 Do not al P231+P232: Ha P363 Wash cor P342+P311 If e	fire spontaneously if exposed to air. et with water releases flammable gas. se allergy or asthma symptoms or breathing difficultie se an allergic skin reaction. ay from heat/sparks/open flames/hot surfaces – No low contact with air. andle under inert gas. Protect from moisture ntaminated clothing before reuse. experiencing respiratory symptoms: Call a POISON
	H250 Catches H H261 In contac H334 May caus if inhaled. H317 May caus P210 Keep awa smoking. P222 Do not al P231+P232: Ha P363 Wash cor P342+P311 If e CENTER or do	fire spontaneously if exposed to air. et with water releases flammable gas. se allergy or asthma symptoms or breathing difficultie se an allergic skin reaction. ay from heat/sparks/open flames/hot surfaces – No low contact with air. andle under inert gas. Protect from moisture ntaminated clothing before reuse. experiencing respiratory symptoms: Call a POISON bector/physician.
	H250 Catches H H261 In contac H334 May caus if inhaled. H317 May caus P210 Keep awa smoking. P222 Do not al P231+P232: Ha P363 Wash cor P342+P311 If e CENTER or do P422 Store con	fire spontaneously if exposed to air. et with water releases flammable gas. se allergy or asthma symptoms or breathing difficultie se an allergic skin reaction. ay from heat/sparks/open flames/hot surfaces – No low contact with air. andle under inert gas. Protect from moisture ntaminated clothing before reuse. experiencing respiratory symptoms: Call a POISON bector/physician. itents under inert gas.
	H250 Catches I H261 In contac H334 May caus if inhaled. H317 May caus P210 Keep awa smoking. P222 Do not al P231+P232: H3 P363 Wash cor P342+P311 If 6 CENTER or do P422 Store con P502 Dispose of	fire spontaneously if exposed to air. et with water releases flammable gas. se allergy or asthma symptoms or breathing difficultie se an allergic skin reaction. ay from heat/sparks/open flames/hot surfaces – No low contact with air. andle under inert gas. Protect from moisture ntaminated clothing before reuse. experiencing respiratory symptoms: Call a POISON octor/physician. itents under inert gas. of contents/container in accordance with
Precautionary Statements:	H250 Catches I H261 In contac H334 May caus if inhaled. H317 May caus P210 Keep awa smoking. P222 Do not al P231+P232: H3 P363 Wash cor P342+P311 If 6 CENTER or do P422 Store con P502 Dispose of	fire spontaneously if exposed to air. et with water releases flammable gas. se allergy or asthma symptoms or breathing difficultie se an allergic skin reaction. ay from heat/sparks/open flames/hot surfaces – No low contact with air. andle under inert gas. Protect from moisture ntaminated clothing before reuse. experiencing respiratory symptoms: Call a POISON bector/physician. itents under inert gas.
	H250 Catches I H261 In contac H334 May caus if inhaled. H317 May caus P210 Keep awa smoking. P222 Do not al P231+P232: H3 P363 Wash cor P342+P311 If 6 CENTER or do P422 Store con P502 Dispose of	fire spontaneously if exposed to air. et with water releases flammable gas. se allergy or asthma symptoms or breathing difficultie se an allergic skin reaction. ay from heat/sparks/open flames/hot surfaces – No low contact with air. andle under inert gas. Protect from moisture ntaminated clothing before reuse. experiencing respiratory symptoms: Call a POISON octor/physician. itents under inert gas. of contents/container in accordance with
Precautionary Statements:	H250 Catches I H261 In contac H334 May caus if inhaled. H317 May caus P210 Keep awa smoking. P222 Do not al P231+P232: H2 P363 Wash cor P342+P311 If of CENTER or do P422 Store con P502 Dispose of local/regional/r	fire spontaneously if exposed to air. et with water releases flammable gas. se allergy or asthma symptoms or breathing difficultie se an allergic skin reaction. ay from heat/sparks/open flames/hot surfaces – No low contact with air. andle under inert gas. Protect from moisture ntaminated clothing before reuse. experiencing respiratory symptoms: Call a POISON octor/physician. tents under inert gas. of contents/container in accordance with national/international regulations.
Precautionary Statements: HMIS Health Ratings (0-4):	H250 Catches H H261 In contac H334 May caus if inhaled. H317 May caus P210 Keep awa smoking. P222 Do not al P231+P232: Ha P363 Wash cor P342+P311 If e CENTER or do P422 Store con P502 Dispose o local/regional/r	fire spontaneously if exposed to air. et with water releases flammable gas. se allergy or asthma symptoms or breathing difficultie se an allergic skin reaction. ay from heat/sparks/open flames/hot surfaces – No low contact with air. andle under inert gas. Protect from moisture ntaminated clothing before reuse. experiencing respiratory symptoms: Call a POISON betor/physician. ttents under inert gas. of contents/container in accordance with national/international regulations. Bulk

3. Composition		
Chemical Family:	Metal alloy	
Additional Names:	None	
Aluminum (Al):		
Percentage:	0-100 wt%	
CAS #:	7429-90-5	
EC #:	231-072-3	
Cobalt (Co):		
Peracentage:	0-100 wt%	
CAS #:	7440-48-4	
EC #:	231-158-0	
	4. First Aid Procedures	
General Treatment:	Seek medical attention if symptoms persist.	
Special Treatment:	None	
Important Symptoms:	None	
Inhalation:	Remove victim to fresh air. Supply oxygen if breathing is difficult.	
	Seek medical attention	
Ingestion:	Seek medical attention	
Skin:	Wash affected area with mild soap and water. Seek medical attention	
Eyes:	Flush eyes with water, blinking often for several minutes. Remove	
	contact lenses if present and easy to do. Continue rinsing	
	5. Firefighting Measures	
Flammability:	Flammable	
Extinguishing Media:	Do not use water for metal fires $-$ use CO ₂ , sand, extinguishing powder.	
Spec. Fire Fighting Procedure:	Use full-face, self-contained breathing apparatus with full protective	
Speet The Tighting Treedure.	clothing to prevent contact with skin and eyes. See section 10 for	
	decomposition products.	
	6. Accidental Release Measures	
If Material Is Released/Spilled:	Wear appropriate respiratory and protective equipment specified in	
	special protection information. Isolate spill area and provide	
	ventilation. Vacuum up spill using a high efficiency particulate	
	absolute (HEPA) air filter and place in a closed container for disposal.	
	Take care not to raise dust.	
Environmental Precautions:	Isolate runoff to prevent environmental pollution.	
	7. Handling and Storage	
Handling Conditions:	Wash thoroughly after handling.	
Storage Conditions:	Store in a cool dry place in a tightly sealed container. Store under inert	
	gas. Store apart from materials and conditions listed in section 10.	
Work/Hygienic Maintenance:	Do not use tobacco or food in work area. Handle under inert gas.	
	Protect from moisture. Wash thoroughly before eating and smoking. Do	
X7	not blow dust off clothing or skin with compressed air. Provide sufficient ventilation to maintain concentration at or below	
Ventilation:		
	threshold limit.	

8. Exposure Controls and Personal Protection		
Permissible Exposure Limits:	0.1 mg/m ³ as Co, long-term value	
Threshold Limit Value:	0.02 mg/m ³ as Co, long-term value	
Special Equipment:	None	
Respiratory Protection:	Use a respirator with type N95 (USA) or PE (EN 143) cartridges as a	
	backup to engineering controls. Risk assessment should be performed	
	to determine if purifying respirators are appropriate. Only use	
	equipment tested and approved under appropriate government	
	standards.	
Protective Gloves:	Nitrile rubber, NBR	
Eye Protection:	Full face protection, Safety glasses or goggles	
Body Protection:	Protective work clothing. Wear close-toed shoes and long	
bouy rotection.	sleeves/pants.	
9.	Physical and Chemical Characteristics	
Color:	Grey	
Form:	Powder	
Odor:	Odorless	
Water Solubility:	powder: Contact with water liberates extremely flammable gases	
Boiling Point:	N/A	
Melting Point:	657-1640 °C	
Flash Point:	N/A	
Autoignition Temperature:	~400 °C for powders	
Density:	N/A	
Molecular weight:	undefined	
	10. Reactivity	
Stability:	Stable under recommended storage conditions	
Reacts With:	N/A	
Incompatible Conditions:	Air, water, moisture, Oxidizing agents Metal oxide fume	
Hazardous Decomposition Products:	Metal oxide lume	
	11. Toxicological Information	
Potential Health Effects:		
Eyes:	May cause irritation	
Skin:	May cause allergic skin reaction	
Ingestion:	May cause irritation	
Inhalation:	May cause irritation	
Chronic:	N/A	
Signs & Symptoms:	N/A	
Aggravated Medical Conditions:	N/A	
Median Lethal Dose:	6171 mg/kg for rat by mouth	
Carcinogen:	 IARC-2B: Possibly carcinogenic to humans: limited evidence in huma in the absence of sufficient evidence in experimental animals. ACGIH A3: Animal carcinogen: Agent is carcinogenic in experimenta animals at a relatively high dose, by routes of administration, at sites, histologic types, or by mechanisms not considered relevant to worker exposure. Available epidemiologic studies do not confirm an increased risk of cancer in exposed humans. Available evidence suggests that the agent is not likely to cause cancer in humans except under uncommon or unlikely routes or level of exposure. 	

•

	12. Ecological Information	
Aquatic Toxicity:	Low	
Persistent Bioaccumulation Toxicity:	No	
Very Persistent, Very Bioaccumulative:	No	
Notes:	N/A	
	13. Disposal Considerations	
Dispose of in accordance with local, state	, national, and international regulations.	
	14. Transportation Data	
Hazardous:	Hazardous as powder only.	
	DANGEROUS REAL	
Hazard Class:	4.3 Substances which, in contact with water, emit flammable gases	
Subclass:	4.1 Flammable solids	
Packing Group:	Ш	
UN Number:	UN3132	
Proper Shipping Name:	Water-reactive solid, flammable, n.o.s. (Aluminum cobalt powder)	
	15. Regulatory Information	
Sec 302 Extremely Hazardous:	No	
Sec 304 Reportable Quantities:	No N/A	
Sec 302 Extremely Hazardous: Sec 304 Reportable Quantities: Sec 313 Toxic Chemicals:	No	

This safety data sheet should be used in conjunction with technical sheets. It does not replace them. The information given is based on our knowledge of this product, at the time of publication. It is given in good faith. The attention of the user is drawn to the possible risks incurred by using the product for any other purpose other than that for which it was intended. This does not in any way excuse the user from knowing and applying all the regulations governing his activity. It is the sole responsibility of the user to take all precautions required in handling the product. The aim of the mandatory regulations mentioned is to help the user to fulfill his obligations regarding the use of hazardous products.

Document Last Revised:

11/13/2019